

Highlights

A Converged Platform of Features and Functionality

- The RFS 4000 is a fully integrated wireless controller appliance, wired switch with 5 POE ports rolled into one, with IPSEC VPN/firewall/WIPS security, RADIUS & DHCP server, 3G failover, and more.

WiNG Architecture

- Improve business process flow with one platform for wireless voice, video, data and multiple RF technologies — Wi-Fi and 4G technologies in the future; rich enterprise-class functionality includes seamless roaming across L2/L3 deployments, resilient failover capabilities, comprehensive security, toll-quality voice and other value-added services.

Guest Access (Hotspot)

- Provides guest access for wired* and wireless clients. built-in captive portal, customizable login/ welcome pages, URL redirection for user login, usage-based charging, dynamic VLAN assignment of clients, DNS white list, GRE tunneling of traffic to central site*, API support for interoperability with custom web portals*

3G Connectivity for Failover or Rapid Deployment

- Support for 3G wireless WAN backhaul with various off the shelf 3G PCI Express cards traffic when the primary WAN Link fails



ExtremeWireless™ WiNG RFS 4000

Wireless Controller Appliance

Product Overview

True Convergence of Wired and Wireless Services for Branch Facilities

The RFS 4000 wireless services controller integrates wired, wireless and security networking features into a compact and easy-to-use form factor, enabling organizations to create survivable branch networks using a single platform. In addition, the RFS 4000 offers built in applications such as IPSec VPN, Firewall, RADIUS & DHCP provide all the necessary services for a branch facility.

Always on Secure Networking

The RFS 4000 offers multiple features that ensure reliability and survivability of branch networking services in virtually any situation. The RFS 4000 protects against access point and mesh node failure with SMART RF, a feature that keeps users on-Net with automatic optimization and healing. WiNG clustering mechanism protects against wireless switch failure and offers Active/Active or Active/Standby controller redundancy options. In the event of a WAN outage, a 3G ExpressCard guarantees Internet services by providing WAN backhaul options. Finally, the RFS 4000 Series displays true convergence by securing both the wireless and wired network with its Integrated Stateful L2-7 Wired/Wireless Firewall, Integrated IDS/IPS engine for Rogue Detection and Containment, Anomaly Analysis engine, DoS Attack protection and Ad-Hoc Network Detection.

Highlights (Cont.)

Enhanced End-to-End Quality of Service (QoS)

- Enhances voice and video capabilities; prioritizes network traffic to minimize latency and provide optimal quality of experience over the wire and over the air; SIP Call Admission Control and Wi-Fi Multimedia Extensions (WMM-Power Save) with Admission Control enhances multimedia application support and improves battery life and capacity

RFS 4000 Part Numbers

- RFS4010-00010-WR: 6 Port RFS 4000 Integrated Services Controller
- RFS-4010-MTKTIU-WR: I RU Mounting Kit
- RFS-4000-6ADP-LIC: 6 AP adoption license
- RFS-4000-12ADP-LIC: 12 AP adoption license
- RFS-4000-24ADP-LIC: 24 AP adoption license
- RFS-4000-48ADP-LIC: 48 AP adoption license

Extremely Simple to Deploy and Manage — No Local IT Support Required

Multiple features combine to eliminate the need for onsite IT support for deployment and day-to-day management, including: built-in intelligence that allows the network to identify and automatically address network issues; zero touch installation; and the integration of all wired and wireless networking infrastructure into a single device that is easily managed back in the NOC via auto-discovery and auto-configuration.

Advanced Services for the Smart Branch

The RFS 4000 not only offers wired and wireless networking and security services, but also value-added and productivity applications. An integrated customizable Guest Access application with distributed or centralized authentication enables a branch network to offer hotspot services for guests. The rich feature set provides granular control over the many wireless networking functions required to deliver high performance, persistent, clear connections with toll-quality voice. Quality of Service (QoS) ensures superior performance for voice and video services. WMM Admission Control, including TSPEC, SIP Call Admission Control, and 802.11k radio resource management, ensures dedicated bandwidth for voice calls as well as better control over active voice calls for a variety of VoIP handsets.

End-to-End Support

As an industry leader in mobility, Extreme offers the experience gained from deploying mobility solutions all over the globe in many of the world's largest enterprises. Leverage this expertise through Extreme Enterprise Mobility Services, which provides the comprehensive support programs you need to deploy and maintain your RFS 4000 at peak performance. Extreme recommends protecting your investment with Service from the Start Advance Exchange Support, a multi-year program that provides the next-business-day device replacement, technical software support and software downloads you need to keep your business running smoothly and productively. This service also includes Comprehensive Coverage, which covers normal wear and tear, as well as internal and external components damaged through accidental breakage — significantly reducing your unforeseen repair expenses.

The RFS 4000 enables distributed enterprises to provide any size branch office with high performance, comprehensive, cost-effective and secure wireless and wired networking services.

For more information about the RFS 4000, please visit www.extremenetworks.com.

Performance and Capacity

Product features	
Supports	
144 Access Points	
144 RF Domains	
24 Wireless LANS	
Physical Characteristics	
Form Factor	<ul style="list-style-type: none"> 1U Rack Mount Tray available
Dimensions	<ul style="list-style-type: none"> 1.75 in. H x 12 in. W x 10 in. D 44.45 mm H x 304.8 mm W x 254.0 mm D
Weight	<ul style="list-style-type: none"> RFS 4010: 4.75 lbs./2.15 kg Antenna facade: 1.45lb
Physical Interfaces	<ul style="list-style-type: none"> 1x Uplink Port -10/100/1000 Cu/Gigabit SFP interface 5x 10/100/1000 Cu Ethernet Ports, 802.3af and, 802.3at Draft 1x USB 2.0 Host 1x ExpressCard™ Slot 1x Serial Port (RJ45 style)
MTBF	<ul style="list-style-type: none"> >65,000 Hours
User Environment	
Operating Temperature	32° F to 104° F /0° C to 40° C
Storage Temperature	-40° F to 158° F/-40° C to 70° C
Operating Humidity	5% to 85% (w/o condensation)
Storage Humidity	5% to 85% (w/o condensation)
Heat Dissipation	95 BTU/hr
Max Operating Altitude	3000m
Management	
AC input voltage	100-240 VAC 50/60Hz
Operating Voltage	44 to 57 VDC
Operating Current	2.5A(max) @48 VDC or 2.2A(max) @ 54 VDC
Max Power Consumption	120W



The Wi-Fi CERTIFIED™ Logo is a certification mark of Wi-Fi Alliance®.



<http://www.extremenetworks.com/contact>

©2019 Extreme Networks, Inc. All rights reserved. Extreme Networks and the Extreme Networks logo are trademarks or registered trademarks of Extreme Networks, Inc. in the United States and/or other countries. All other names are the property of their respective owners. For additional information on Extreme Networks Trademarks please see <http://www.extremenetworks.com/company/legal/trademarks>. Specifications and product availability are subject to change without notice. 11223-0217-16